

CHORUS 816 V

Product specification sheet

Aluminum/Magnesium inverted dome TNV tweeter.
Extended response to 28kHz, ready for SACD.

6¹/₂" (165mm) Polyglass midbass.
Highly dynamic medium.

6¹/₂" (165mm) Polyglass woofer.
High power handling.

Front-firing port for bass impact.
Powerflow™ multiport system.
Powerful bass.

Down-firing port for deep bass.





Acrylic core, black mirror effect.
Exclusive finish.

Solid MDF construction
up to 1" (25mm) width.
Non parallel inner wall structure.

OPC crossover.
Perfect staging.
New insulated Focal terminals.

Cast Aluminum base.
Stable base.
Adjustable spikes with key.



- ◆ High-end design, affordable luxury.
- ◆ Speakers designed and manufactured by Focal.

- ◆ A sound quality never before seen at this price level.
- ◆ Acrylic core, 2 side finishes ; Moka and Ebony.

Type	2 1/2-way bass-reflex floorstanding loudspeaker
Drivers	6 ¹ / ₂ " (165mm) Polyglass woofer 6 ¹ / ₂ " (165mm) Polyglass mid-bass 1" (25mm) TNV Al/Mg inverted dome tweeter
Frequency response (+/- 3dB)	47Hz - 28kHz
Low frequency point (- 6dB)	39Hz
Sensitivity (2.83V/1m)	91.5dB
Nom. impedance	8 ohms
Minimum impedance (@25°C)	4.3 ohms @ 146Hz
Max. power handling.	200W
Power RMS	130W
Crossover frequency	300Hz / 3kHz
Dimensions (HxWxD)	39 ⁵ / ₁₆ " x 11 ¹ / ₈ " x 14 ³ / ₄ " [998x282x375mm]
Net weight	49.5lbs [22.5kg]

Chorus 816 V makes the most of the 2 and a half-way configuration: elevated performance in lower octaves thanks to the combination of woofers working in unison. Up to 30 m².



FOCAL
the spirit of sound