



CHORUS SR 800 V

Product specification sheet



- ◆ High-end design, affordable luxury.
- ◆ Speakers designed and manufactured by Focal.

- ◆ A sound quality never before seen at this price level.
- ◆ Acrylic core, Black satin finish.

Type	2-way sealed bipolar effects loudspeaker, Polyfix™ wall bracket
Drivers	2x5" (130mm) Polyglass mid-bass 2x1" (25mm) TNV Al/Mg inverted dome tweeter
Frequency response (+/- 3dB)	75Hz - 28kHz
Low frequency point (- 6dB)	65Hz
Sensitivity (2.83V/1m)	90dB
Nom. impedance	8 ohms
Minimum impedance (@25°C)	3.7 ohms @ 210Hz
Max. power handling	120W
Power RMS	80W
Crossover frequency	3kHz
Dimensions (HxWxD)	11 ^{7/16} " x 15 ^{3/4} " x 6 ^{7/8} " [290x400x175mm]
Net weight	12.3lbs (5.6kg)

The capacity of the Chorus SR 800 V to fill surround space with precision is spectacular. Its behavior is optimized thanks to the integrated "Wall Boost Control" and with an exacting directivity. Compact, discrete, but Chorus in its spirit with an acrylic finish.

